

Scouring machine EPF 1503



Ø 140



Concrete grinder EBS 120.1



Ø 125



The specialist scouring machine with a high removal rate

USE:

- Removal of tile adhesive, plaster, paint, coatings
- Roughing of surfaces

FEATURES:

- Electronic – soft start, constant speed, speed reduction in case of overload, temperature control and over current cut-off
- Guide ring adjustable – precise depth definition
- Brush rim – high suction power for dust-free working by connecting an industrial vacuum cleaner (accessory) to the 35 mm nozzle
- Soft grip handle – less vibration, non-slip

The compact

USE:

- Grinding and smoothing of surfaces
- Removing of screed seams, residual mud, plaster and coatings
- Preparing of surfaces, e.g. for tile renovation
- Working in tight spots for example under radiators and on protrusions
- Concrete, screed, tile adhesive, plaster, paint, coatings, carpet adhesive – with corresponding grinding wheels (accessories)

FEATURES:

- Foldable front edge of dust guard – for grinding directly to the edge of the work area
- Brush rim – high suction power for dust-free working by connecting an industrial vacuum cleaner (accessory)
- Slim housing design – compact, well balanced design
- Soft grip handle – less vibration, non-slip
- Spindle lock – easy tool change

SPECIFICATIONS	EPF 1503
Power input	1500 W
Rated voltage	230 V ~
Rated speed	4000 rpm
Milling head diameter	140 mm
Depth adjustment	0.5-4.0 mm
Spindle connection	M 14 male
Weight	3.9 kg
Order no.	06511000

Supplied in a case incl. capstan with 16 claw cutters (bent)

SPECIFICATIONS	EBS 120.1
Power input	1400 W
Rated voltage	230 V ~
No-load speed	9000 rpm
Disc diameter	125 mm
Spindle connection	Ø 22.2 mm
Weight	3.5 kg
Order no.	0630P000

Supplied in a case incl. diamond-grinding wheel (concrete) and assembly tools

