

## Industrial vacuum cleaner DSS 25 A

### The compact wet and dry cleaners

#### APPLICATION:

- Vacuuming of sludges (wet)
- Cleaning of cars, living and business rooms

#### FEATURES:

- Automatic filter cleaning (electromagnetic pulse)
  - cleaning of the filter, working without, complete dedusting of the cartridges
- Electronic – soft start with deferred rundown switching
- Flow rate indicator – optical monitoring of the suction performance
- Consistently high flow rate – increases filter life, reduction of time and costs
- Water recognition with sensor disconnection
- 2 polyester filter cassettes – high efficiency, durable, easy to clean
- Filter surface 8600 cm<sup>2</sup> – high constant suction performance
- Compact design – smaller height, same volume
- Special-plastic tank – low centre of gravity, easy cleaning of walls
- Large storage tray for accessories and machines
- Hose connection with bayonet and twist balancing
- Hose ends are interchangeable – easy hose extension, dust free transport

25 l



SPECIFICATIONS	DSS 25 A
Max. power input	1400 W
Rated voltage	230 V ~
Tank volume (max.)	25 l
Dust volume (net)	20 l
Max. air flow	73 l/s
Max. vacuum	270 mbar
Dimensions L x B x H (mm)	457 x 400 x 535
Weight	11.7 kg
Order no.	09915000

Supplied: in a box incl. 5 m suction hose (Ø 35 mm), universal-adaptor, nozzle for floor and crevices, handle tube with air switch, 2 suction tubes (plastic), velcro strip, holder for accessories

