# E EIBENSTOCK

Made in Germany

**Quality power tools since 1919** 



The innovative VacuGlide-Sanding System

### The innovative VacuGlide-Sanding System

### Effort- and time-saving sanding of ceilings and walls

Our technology makes it easier: You work with only about 1.5 kg\* weight and therefore more relaxed and for a longer time compared to existing solutions. This serves the health, saves time and costs due to a maximum area finishing.


The long reach sander ELS 225.1 is developed and designed together with professional dry-wall constructors. The VacuGlide-System (in conjunction with EIBENSTOCK industrial vacuum cleaners) allows to hold the sander through the suction force at the ceiling or wall but nevertheless to guide on the surface without any problems. The sander mainly just has to be guided.

Additionally the VacuGlide-Sanding System relieves the operator from the permanent exhausting pressing. In addition the removal rate can be adjusted variably.

Besides the sanding of putty areas in the dry-wall construction sector a large number of further sanding operations for renovating and painting works can be carried out, for example the removing of wallpaper residues or the sanding of thermal insulations. You receive perfect results for every application.

#### strenuous was yesterday





### lightweight is today



### VacuGlide-System

- stress-relieved sanding of ceilings and walls
- more than 60% less effort in comparison to comparable sanding solutions
- higher work efficiency in daily work
- prevention of pain in the back, neck and shoulder
- relaxed working on high ceilings

ELS 225.1 + DSS 25/50 A



**PROTECTION HEALTH** 











 Spring-mounted suction hood with sealing lip VacuGlide

optimal adaptation to the surface

- compensates unevenness
- prevents grooving when starting to sand

efficient dust extraction through the hood and perforated sanding disc

sealing lip exchangeable against brush rim for other sanding operations

- VacuGlide System Adjustment of the suction capacity and contact pressure – for a better guiding of the sander on the surface, adaptation of the removal rate
- Robust joint optimum adaptation to inclination and angle
- Rubber foam pad achieves very smooth surfaces
- Electronic soft start, electronic overload protection
- Dust-protected on/off switch and setting wheel for variable speed selection – optimum adaptation of the speed to the surface

**Extension for high ceilings and walls (up to about 3 m)** – easy mounting, no additional devices required such as ladder or scaffolding, time saving

- Lightweight, balanced and ergonomic design

   easy to use, effortlessly sanding, numerous grip positions
- Additional handle ergonomic handling, variably adjustable at the machine (accessory)













Specifications	Long reach sander ELS 225.1
Power input	590 W
Rated voltage	230 V ~
Rated speed	1,050-1,600 rpm
Disc diameter	225 mm
Spindle connection	M 14 (velcro)
Weight	4.9 kg
Order No.	0620N000
Supplied	in a box with transport bag, extension, sanding pad starter kit (1x P80/P100/P120) and brush rim



## **EIBENSTOCK**



### **Quality power tools since 1919**

Accessory	Description	Order No.
	Base plate (velcro) 6-hole punch	37631000
	Rubber foam pad (velcro) 6-hole punch	37632000
	Sanding pad (velcro) perforated (10 pcs) P40 P60 P80 P100 P120 P150 P180 P220	37672000 37673000 37674000 37675000 37676000 37677000 37678000 37679000
	Sanding grid (velcro) 6-hole punch (10 pcs) P80 P120	37610000 37611000
	Sandpaper (velcro) 6-hole punch P24 - Semi-friable corundum (10 pcs) P40 - Normal corundum (25 pcs) P60 - Normal corundum (25 pcs) P80 - Normal corundum (25 pcs) P100 - Normal corundum (25 pcs) P120 - Normal corundum (25 pcs)	37608000 37642000 37643000 37644000 37645000 37646000
	P150 - Normal corundum (25 pcs) P180 - Normal corundum (25 pcs) P220 - Normal corundum (25 pcs)	37647000 37648000 37649000
	Sandpaper assortment (velcro) 6-hole punch (5 pcs each) P80/100/120/150/180	37640000
	Brush rim	3722B000
	Sealing lip VacuGlide	3722C000
-	Additional handle	37659000
	Flexible shaft	7620L598

#### **Furthermore we recommend:**

for all EIBENSTOCK-machines with dust extraction our industrial vacuum cleaner with a high, constant suction performance



DSS 25 A - wet/dry 1,400 W, 25 l tank volume	09915000
DSS 50 A - wet/dry 1,400 W, 50 l tank volume	09916000

for grinding close to the edge of the working area our light and handy dry-wall specialist



Dry-wall sander ETS 225 700 W, 225 mm disc-Ø	06203000

for the fixing of construction boards and other installation work our powerful dry-wall screwdriver



Dry-wall screwdriver ESR 450 450 W, 5 mm screw-Ø	06102000
Dry-wall screwdriver ESR 500 500 W, 5 mm screw-Ø	06101000

for the mixing of filler and levelling compounds up to 40 kg our universal stirrer





### EIBENSTOCK

Elektrowerkzeuge GmbH Eibenstock Auersbergstraße 10 08309 Eibenstock, Germany

Phone: +49 (0) 3 77 52 - 50 30 Fax: +49 (0) 3 77 52 - 20 19 Internet: www.eibenstock.com E-Mail: office@ee-eibenstock.de Your specialized dealer:

9272000 - 07/15