



The universal stirrer up to 40 kg

USE:

- Mixing of building materials with low and middle viscosity, e.g. paint, glue, filler and leveling compounds, tile cement, ready-mixed mortar
- Drywall construction, tiler, painter and plasterer, civil engineering

FEATURES:

- Electronic switch stepless speed regulation for less splashing
- Cap with labyrinth-guide protection against dust, dirt, stones, splash water
- M 14 female direct stirrer connection effective power transmission, high concentricity

EHR 18 S SET

1,100 W

230 V ~

120 mm

4.1 kg

M 14 female

07741000

with stirring rod WG 120

in a box

0-450 rpm 800 rpm

- Damping and protection elements

SPECIFICATIONS Power input

Rated voltage

Rated speed

Weight

Order no.

Supplied

No-load speed Max. basket Ø

Spindle connection

N	Stirrer	
	EHR 20.1 R Set	



The perfect adjustable stirrer up to 50 kg

USE:

- Mixing of building materials with middle and high viscosity e.g. filler and leveling compounds, tile cement, ready-mixed mortar and plaster
- Drywall construction, plaster, civil engineering, landscaping

FEATURES:

- Soft start for less splashing
- Temperature control
- Stepless speed regulation and constant speed optimum settings on the material to be mixed
- M 14 female direct stirrer connection effective power transmission, high concentricity
- Cap with labyrinth-guide protection against dust, dirt, stones, splash water
- Damping and protection elements

SPECIFICATIONS	EHR 20.1 R SET
Power input	1,300 W
Rated voltage	230 V ~
Rated speed	250-580 rpm
Max. basket Ø	140 mm
Spindle connection	M 14 female
Weight	4.9 kg
Order no.	07742000
Supplied	in a box with stirring rod MG 140

