

PROFESSIONAL SINCE 1919



# MIDIE MANGSMICH

FloorMix 2300
The economical alternative



Elektrowerkzeuge GmbH Eibenstock Auersbergstraße 10 08309 Eibenstock, Germany

(i) eibenstock.com

Technical changes excepted! Illustrations may vary!

# **NEW** The mobile station up to 150 kg for effective working especially in wet-on-wet cycle

#### **Optimal mixing results:**



Four speed settings, soft start and constant speed – start mixing function with reduced speed and optimal adjustment of the speed to the mixing material



Special stirring rod avoids clumping and material deposits on the base and

### USE:

Homogenous and lump free mixing of floating screed, leveling fillers, fiberreinforced fillers, colored coatings, liquid plastics

## Optimally suited for low-viscosity flooring compounds

Floor renovators, tilers







Connection for dust exhaust  $\emptyset$  35 mm – dust reduced filling and mixing of the materials

#### Easy to clean:





Drive unit with stirring rod can be separated from the carriage without any tools



Specifications	FloorMix 2300
Power input	2300 W
Rated voltage	230 V ~
Rated speed	70/130/160/280 rpm
Bucket size	1101
Spindle connection	M 16
Weight	48.0 kg
Order no.	07625000
Supplied	on a pallet incl. special stirring rod and bucket 110 l

Your distributor: