







## USE:

- Grinding of screed seams
- Removing of burrs, bumps, paint and thin adhesives
- Smoothing of concrete and plaster surfaces

## **FEATURES:**

- Electronic soft start, constant speed, temperature control and over current cut-off
- Exchangeable flexible drive shaft short design, easy to service
- Robust joint optimal adaptation to inclination and angle
- Foldable front edge of dust guard for grinding directly to the edge of the work area
- Extraction nozzle Ø 35 mm (rotatable) direct connection of an M-cleaner of the EIBENSTOCK DSS series
- Locking for suction hose avoids unintentional loosening of the hose during grinding
- Additional handle ergonomic handling, variably adjustable at the machine

Specifications	ELS 125 D
Power input	1200 W
Rated voltage	230 V ~
Rated speed	8000 rpm
Disc diameter	125 mm
Spindle connection	Ø 22.2 mm
Weight	5.3 kg
Order no.	06231000
Supplied in a box incl. transport bag, diamond-grinding	

Supplied in a box incl. transport bag, diamond-grinding wheel universal and assembly tools

Elektrowerkzeuge GmbH Eibenstock Auersbergstraße 10 08309 Eibenstock, Germany

Phone: +49 (0) 3 77 52 - 50 30 Fax: +49 (0) 3 77 52 - 20 19 Internet: www.eibenstock.com E-Mail: office@eibenstock.com

Certified according to DIN EN ISO 9001:2015
Technical changes excepted! Illustrations may vary!

Your distributor: